



TYPICAL CUT THROUGH DETAIL

AMENDMENTS		
No.	DESCRIPTION	APPROVED & DATE
5	REFERENCE TO RED ASPHALT REMOVED. DIMENSION AMENDED.	C.M. 16/08/2018
6	TITLE BLOCK AND FILE No. UPDATED. NOTE 8. ADDED.	C. M. 03/03/2026

- NOTES
1. THE DROP DOWN CUT THROUGH TREATMENT SHOULD ALLOW FOR SIGNAL POLES TO BE SET BACK DESIRABLY 1.4m FROM THE KERB LINE. THE 1.4m ALLOWS FOR 300mm SET BACK TO THE TGSi, 800mm OF TGSi AND THE SIGNAL POLE BEING 300mm FURTHER BACK FROM THE TGSi.
 2. WHEN DEVELOPING THE TREATMENTS PLEASE CAREFULLY CONSIDER THE DRAINAGE REQUIREMENTS. THERE ARE A VARIETY OF PEDESTRIAN FRIENDLY SYSTEMS THAT CAN BE INSTALLED WITHIN THE CUT THROUGH AREA AND IN EXTREME CASES ADDITIONAL SIDE ENTRY PITS MAY BE REQUIRED ON ROAD.
 3. A MINIMUM 30% LUMINANCE CONTRAST BETWEEN THE COLOUR OF THE PATH AND THE COLOUR OF THE TGSi MUST BE ACHIEVED.
 4. ALL PITS TO BE LOWERED AND MADE FLUSH WITH NEW PATH LEVEL.
 5. THIS TREATMENT IS TO BE USED IN RESTRICTED LOCATIONS WHERE TYPE 'A' AND 'B' RAMPS ARE NOT FEASIBLE.
 6. THE TACTILE INDICATORS SHOULD BE ALIGNED TO BE AT RIGHT ANGLES TO THE INTENDED DIRECTION OF PEDESTRIAN TRAVEL.
 7. TGSIs CAN BE EITHER 300 x 300mm OR 400 x 400mm IN SIZE. (400 x 400mm TILES SHOWN).
 8. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS STATED OTHERWISE.



AREA TO BE INFILLED WITH PAVING AND/OR CONCRETE

PLANNING AND TECHNICAL SERVICES DIRECTORATE ROAD AND TRAFFIC ENGINEERING BRANCH Waterloo Crescent EAST PERTH 6004 Telephone 138 138	
DRAWN	C. MAGRIPLIS APRIL 09
DESIGNED	C. MAGRIPLIS APRIL 09
VERIFIED	C. MAGRIPLIS 07/01/10
APPROVED	R. GROVE 07/01/10
FILE NO.	13/4330

STANDARD DRAWING
TACTILE GROUND SURFACE INDICATORS
MODIFIED CUT THROUGH CORNER

MRWA DRAWING NUMBER 200931-0090-6 AMENDMENT

SCALES 1:100 0 0.5m 1 1.5 2 2.5 3 3.5 4 4.5 5 5.5 6 6.5 7 7.5
 A 3