


ZEBRA CROSSING SETTING OUT DETAIL N.T.S



DESCRIPTION	APPROVED & DATE
SIGNS MODIFIED AND NOTE 4 ADDED. TGSI'S ADDED. NOTE 2 AMENDED, NOTE 3 ADDED. NOTE 4 AMENDED, MATE 3 ADDED. NOTE 2 AMENDED, MARKINGS REMOVED FROM NICH SPEED LIMIT EXAMPLE, FREE FLOWING SLIP LANE EXAMPLE ADDED.	R. KOORENCEVEL 53.90 R. KOORENCEVEL 53.90 D. LANDHARK 1.11.13 R. KOORENCEVEL 19.3.14 LEWENS J. J. L.

NOTES

- PAVEMENT MARKINGS TO BE INSTALLED AS PER SPECIFICATION 604.
- 2. FOR FREE LEFT-TURN SLIP LANES IF THE 85th PERCENTILE APPROACH SPEED IS LESS THAN 60km/h, SIGNAGE AND ZEBRA CROSSING MARKINGS ARE IDENTICAL TO HIGH-ANGLE ENTRY CASE SHOWN.
- FOR FREE LEFT-TURN SLIP LANES WHERE THE 85th PERCENTILE APPROACH SPEED IS GREATER THAN 60km/h, NO PEDESTRIAN CROSSING MARKINGS OR GUIDE LINES ARE TO BE INSTALLED.
- . IF LENGTH OF TURN POCKET (EXCLUDING TAPER) IS LESS THAN 100m, INSTALL W6-2B SIGN APPROX. 20m FROM END OF TAPER.
- FOR SLIP LANES LESS THAN 5.4m WIDE THE WIDTH OF THE BARS CAN BE REDUCED TO 500mm AND THE WIDTH OF THE GAP REDUCED TO 450mm TO ENSURE THE MINIMUM NUMBER OF BARS IS DISPLAYED.



Western Australia

Western Australia

19.6.06

TECHNOLOGY AND ENVIRONMENT
ROAD AND TRAFFIC ENGINEERING Waterloo Crescent Telephone (08) 9323 4111 East Perth 6004 Fax (08) 9323 4449

67-08-5

S. NAUMOVSKI/J. COOK JUL.'05 D. LANDMARK 16.6.06

R. GROVE

STANDARD DRAWING

ZEBRA CROSSING AT SLIP LANE

LOCAL AUTHORI

200531-0038-5