



AMENDMENTS		
No.	DESCRIPTION	APPROVED & DATE
4	AMENDED WARDENS FLAG MR-RP-9 AND PEDESTRIAN MARKINGS ADDED.	R.V. 9.2.01
5	PAVEMENT MARKINGS, TITLE BLOCK AMENDED. NOTE 5 ADDED. BOLLARD SIZE CHANGED GRADE OF STEEL ADDED.	D. LANDMARK 23.5.07
6	PEDESTRIAN MARKINGS AMENDED.	D. LANDMARK 14.10.09
7	UNBROKEN SEPARATION LINE ON APPROACH TO PEDESTRIAN ISLAND REPLACED BY OUTLINE MARKINGS. BIDIRECTIONAL RRPM's REPLACED WITH UNIDIRECTIONAL RRPM's. NOTE 5 REMOVED.	D. LANDMARK 8.4.10
8	1.5m HIGH HOLES ADDED TO POST FOR FLAG. TGS's AND NOTE 5 ADDED.	D. LANDMARK 20.1.12
9	KEEP CLEAR PAVEMENT MARKING AND NOTE 6 ADDED.	D. LANDMARK 16.11.14
10	PLAN WITHOUT PEDESTRIAN ISLAND ADDED. PLAN WITH PEDESTRIAN ISLAND AND TABLE 1 AMENDED. NOTES 7 AND 8 ADDED.	R. KOORENGEVEL 9.5.16
11	COLOR CORRECTED ON WARNING SIGNS & FLAGS.	R. KOORENGEVEL 15.7.16
12	LENGTH OF PEDESTRIAN MARKINGS CHANGED TO 1m.	R. KOORENGEVEL 22.17
13	TYPICAL REFUGE WIDTH AND FLUORESCENT YELLOW/GREEN SCHOOL SIGN COLOUR AMENDED.	E. ROSE 20.2.19
14	NOTES 10 & 11 ADDED. LOCATION OF BOLLARDS AND PED. CROSSING WIDTH AMENDED. TABLE 1 AMENDED.	<i>[Signature]</i> 14/1/21
NOTES		
<p>1. TOTAL 24 HOUR PARKING RESTRICTIONS TO BE APPLIED.</p> <p>2. TWIN ALTERNATING YELLOW FLASHING SIGNALS MAY BE USED TO SUPPLEMENT 1.8m BOLLARDS. (SEE DRAWING 9531-2169)</p> <p>3. W8-14B SIGN USED WHERE CROSSING IS ADJACENT TO A SCHOOL OR WITHIN A SCHOOL 40 OR 60 Km/h ZONE.</p> <p>4. CHILDREN CROSSING FLAGS R3-3 TO BE PLACED WHEN TRAFFIC WARDEN IN ATTENDANCE.</p> <p>5. ON ROADS WHERE THE INSTALLATION OF TRANSVERSE MARKINGS IS LIKELY TO CREATE NOISE PROBLEMS (eg. VERY SMOOTH ASPHALT IN RESIDENTIAL AREAS) TRANSVERSE MARKINGS SHOULD BE INSTALLED USING COLD APPLIED PLASTIC 500-700 MICRONS THICK AND WITH 0.5-1.0mm AGGREGATE (WHITE FUSED ALUMINA) FOR SKID RESISTANCE.</p> <p>6. KEEP CLEAR MARKINGS ONLY TO BE USED ON THE LANE WHERE MOTORISTS ARE CONSTANTLY STACKING OVER THE CHILDREN'S CROSSING. FOR DETAILS OF 'KEEP CLEAR' MARKINGS REFER TO FIG 5.13 IN A.S. 1742.2.</p> <p>7. A MINIMUM OF TWO MODULES OF BROKEN SEPARATION LINE (24m) SHALL PRECEDE THE UNBROKEN SEPARATION LINE OR ISLAND OUTLINE MARKINGS. LINES TO BE 120mm WIDE.</p> <p>8. LENGTH OF OUTLINE MARKINGS DEPENDS ON POSTED SPEED LIMIT AND WIDTH OF SPLITTER ISLAND. FOR POSTED SPEED $\leq 60\text{km/h}$, REFER TO DWG No 200331-0184. FOR POSTED SPEED $\geq 70\text{km/h}$, REFER TO DWG No 201031-0004. FOR SPLITTER ISLAND $>3\text{m}$ WIDTH, REFER TO DWG No 200331-0191.</p> <p>9. FOR GRABRAIL REQUIREMENTS REFER DRAWING NUMBER 9831-5649.</p> <p>10. BOLLARDS TO BE LOCATED OUTSIDE WINGWALLS.</p> <p>11. PEDESTRIAN GUIDE LINES TO LINE UP WITH THE OUTSIDE OF TGS's.</p>		
<div><div><p>Government of Western Australia</p></div><div><p>mainroads WESTERN AUSTRALIA</p></div></div> <p>PLANNING AND TECHNICAL SERVICES DIRECTORATE ROAD AND TRAFFIC ENGINEERING</p> <p>WATERLOO CRESCENT EAST PERTH 6004 Telephone (08) 9323 4111 Fax (08) 9323 4449</p>		
FILE NUMBER	30-525-102	
DESIGNED / DRAWN	C. WOOLDRIDGE	22.5.91
VERIFIED	T. HAZEBROEK	25.6.92
APPROVED	P. WAUGH	11.6.91
<p>STANDARD DRAWING TRAFFIC WARDEN CONTROLLED CHILDRENS CROSSING STATIC SIGN SIGNS AND PAVEMENT MARKING</p>		
LOCAL AUTHORITY	AMENDMENT	
DRAWING NUMBER	9120-0174-14	