



POWER SUPPLY
 INPUT VOLTAGE - 110V AC OR 240V AC (+/- 10%) - 48 Hz TO 52 Hz - TO SUIT SUPPLY VOLTAGE
 OUTPUT VOLTAGE - 12V DC REGULATED (+/- 10% MAXIMUM VARIATION)
 OUTPUT CURRENT - UP TO 1.5A
 OUTPUT PROTECTION - SHORT CIRCUIT PROOF
 AMBIENT TEMPERATURE - -10 DEGREES C TO +65 DEGREES C
 OPERATING TEMPERATURE - MAX +90 DEGREES C
 OPERATING MODE - INTERMITTENT FLASHING AT APPROXIMATELY 1 Hz WITH 50% DUTY CYCLE
 INSULATION - FULLY SEALED - IP68

AMENDMENTS		
No.	DESCRIPTION	APPROVED & DATE

- NOTES**
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH SPECIFICATION 712.
 - FOR TYPICAL LAYOUT SEE DRG No. 200431-0104 & 200431-0105.
 - FOR ELV LAMP SIGN WIRING SEE DRG No. 200431-0101.

MAIN ROADS
 Western Australia
 TECHNOLOGY AND ENVIRONMENT
ROAD AND TRAFFIC ENGINEERING
 Waterloo Crescent East Perth 6004
 Telephone (08) 9323 4111 Fax (08) 9323 4449

FILE NUMBER	67-08-4F
DESIGNED / DRAWN	F. WINKLER / K. GREEDA
VERIFIED	B. CHAREHJOO <i>06/11/06</i>
APPROVED	<i>B. Charehjoor</i> 21/10/07

STANDARD DRAWING
 ADVANCE WARNING FLASHING SIGNS
LED SIGNAL LANTERNS
 WIRING DETAILS

DRAWING TYPE	DRAWING NUMBER	AMEND
	200431-0102	

SCALE N.T.S.
 MICROFILM DATE A 3