



Heavy Lift Tow Truck Period Permit Supporting Evidence & Eligibility Checklist

Pre-permit Requirement	Supporting Evidence Required	Evidence Attached	Qualified (Office use only)
The heavy lift tow truck must be installed with an approved in-vehicle telematics unit monitored via a Transport Certification Australia (TCA) approved service provider. Main Roads Heavy Vehicle Services (HVS) must be provided continuous direct access to the associated telematics monitoring system, with the ability to: (a) Identify the position of the heavy lift tow truck, with position records updated every 30 seconds as a minimum; and (b) View data no more than one week old and up to 12 months old.	 Written confirmation from the nominated TCA approved Service Provider the heavy lift tow truck is fitted with an in-vehicle telematics unit and position records are updated every 30 seconds and data viewing is no more than one week old and up to 12 months old. HVS is provided login details to the relevant telematics monitoring system, including a demonstration provided by either the Service Provider and/or operator (if required). 	Yes □	Yes □ No □
The heavy lift tow truck must be installed with an approved on-board mass management (OBM) system, linked to the in-vehicle telematics unit, and monitored via a TCA approved service provider. HVS must be provided continuous access to the OBM system, with the ability to: (a) Download automated mass reports, showing the mass of each individual axle group of the heavy lift tow truck, including location, date and time of the recording. Data transfer must be at least once every 30 minutes; and (b) View data no more than one week old and up to 12 months old.	 Written confirmation from the nominated TCA approved Service Provider the heavy lift tow truck is fitted with an OBM system, linked to the in-vehicle telematics unit and mass data is transferred at least once every 30 minutes and data viewing is no more than one week old and up to 12 months old. HVS is provided login details to the relevant OBM system, including a demonstration provided by either the Service Provider and/or operator (if required). 	Yes □	Yes □ No □
One rear-facing camera must be mounted on the heavy lift tow truck. The rear facing camera must be mounted on the vehicle so that the camera records a clear field of vision of any load the vehicle is towing. The camera must be maintained in good working order.	 Photographic evidence clearly showing the heavy lift tow truck registration and installed rear-facing camera; or Written confirmation from the independent installer. 	Yes □	Yes □ No □