



Australian Government



BUILDING OUR FUTURE

Swan River Crossings Forum 25th November 2020

Welcome

Facilitator: Nicole Lockwood

Start Activity

- 11:00** Welcome, purpose and process
- 11:10** Alignment Forum #1 summary
- 11:20** Repurposing the traffic bridge
- 12:05** Building between the bridges
- 12:50** Lunch
- 1:10** Building to the west
- 1:55** Building to the east
- 2:40** Opportunities and outstanding issues
- 3:25** Next Steps, Closing and Acknowledgments
- 3:45** Forum close

Responsibility

- Nicole Lockwood
- Gary Manning
- Julia Summers (ARUP Civil Structures)
- Lance Thomas/Richard Thomas/Peter Satie/Sue Hellyer
- All
- Lance Thomas/Richard Thomas/Sue Hellyer
- Lance Thomas
- All
- Nicole Lockwood

Alignment Forum #1


Alignment Forum #1 summary

- Held here at the Esplanade in Fremantle on 23rd Oct 2020
- Attended by 25 community representatives as well as stakeholders and technical experts
- Inform the community about project objectives, constraints and background
- Explain the work completed to date, and how we undertook the options assessment process to get to the project team's preferred alignment
- Share other options including City of Fremantle and Andrew Sullivan's
- Identify community drivers and preferred way forward

Alignment Forum #1 summary

- What we heard
 - Community sentiment not supportive of a bridge to the east of the existing traffic bridge. Keen to maintain as much of the heritage structure as possible
 - Need to further analyse other options:
 - Retaining the existing traffic bridge as a principal shared path
 - No new rail bridge
 - Build between the bridges (one rail line bridge and road bridge)
 - Build to the west (two rail line bridge and road bridge)
- Today
 - Explain/discuss the outcome of the investigations into all 4 options
 - Compare/discuss the findings against the preferred option and project objectives
 - Explain alliance contracting and process

Repurposing the traffic bridge



1909

'Renovated high level bridge' built

1939

Fremantle Traffic Bridge built immediately west of 1909 bridge

29-span bridge, 223m timber hybrid structure

25 spans with timber girders

3 navigation spans (2 currently in use) and 1 road span over Beach Street with steel girders

1947


Aerial image (above left) showing both high level and Fremantle Traffic Bridge



1947-1954

High level bridge demolished 1947-1954

2020

Aerial image (left) showing Fremantle Traffic Bridge and Fremantle Rail Bridge





1939
Timber piles – driven 20 ft into the river bed Timber bracing
Pile protection in river via sand-filled concrete pipes
Non-navigation spans Timber deck beam supports (half-cap and corbel) Timber deck beams (stringers) Timber decking (bearers and deck)
Navigation spans Timber and steel deck beam supports Steel deck beams Timber decking
Piled timber fenders at navigation channels
Concrete abutments
Timber guard rails




2020
Rotten piles repaired with steel sections surrounded by concrete and other methods
Various repairs – some concrete pots, sand replaced with grout
Half-caps replaced with steel Concrete deck overlay
Additional horizontal bracing added (concrete beam and steel rods) Concrete deck overlay
Steel and timber fender system and navigation channels
As constructed with minor repairs / additional retaining walls
Steel guard rails



Timber design life – 40 years



Horizontal splint bolts



Deck – road and shared path








Access for maintenance & inspection




Above and below water durability





- 1. Scour
- 2. Marine borers - teredo
- 3. River bed condition

Lowest clearance (vertical and horizontal between Barrack Street and the Indian Ocean)




Mis-aligned piers





Multiple impacts evident

Piers weak against vessel impact.

Fender system has limited capacity



1. Replace Navigation spans – increased horizontal and vertical clearance
2. Replace structure below water
3. Replace deck
4. Potential to re-use timber piers noting the ongoing maintenance for asset owner



Building between the bridges – No rail bridge













Key components

1. Road bridge (four lanes)
2. Pedestrian and cyclist path to go under Queen Victoria Street, north of the northern abutment
3. Pedestrian and cyclist path on new bridge

Key considerations

1. Does not meet project objective regarding improved rail capacity
2. Will require new traffic bridge to be higher to provide long term increased navigational clearance and to enable PSP to pass beneath Queen Victoria street, north of the northern abutment.
3. Reduced storage capacity for vehicles at Beach Street / Canning Highway / Queen Victoria street intersection resulting in significant congestion.

	Environmental consideration		Residential consideration
	Heritage consideration		Proposed road alignment
	Port consideration		Proposed PSP alignment
	Rail consideration		Proposed road bridge
	Road consideration		
	Navigation consideration		

For illustrative purposes only



BETWEEN THE BRIDGES – No rail line and road bridge

Strengths

- No impact to port operations
- Able to construct new traffic bridge between existing bridges
- Bridge across the river moves further away from Rivershore Place (south facing) apartments (approximately 10m)

Weaknesses

- No improvements to rail capacity resulting in significant increase in trucks on road
- PSP on the eastern side - New traffic bridge will need to be approx. 4m higher to allow for PSP underpass. This will impact access to local businesses on Queen Victoria Street and have significant visual impact on west facing Rivershore Place apartments
- Brings traffic light intersections at Canning Highway and Beach Street closer together and will increase congestion and traffic queuing during peak once complete
- Removal of heritage Ferry Capstan Base

BETWEEN THE BRIDGES – One rail line bridge and road bridge

Alternatives

- PSP can be constructed on western side of road bridge resulting in minimal need to raise bridge profile, minimised impact on access to local businesses on Queen Victoria Street

Building between the bridges – One rail line bridge and road bridge













For illustrative purposes only

Key component

1. Rai Bridge (one line)
2. Road bridge (four lanes)
3. Pedestrian and cyclist path to go under Queen Victoria Street, north of the northern abutment
4. Pedestrian and cyclist path on new bridge OR option to position on retained Fremantle Traffic Bridge

Key considerations

1. Will require new traffic bridge to be higher to provide long term increased navigational clearance and to enable PSP to pass beneath Queen Victoria street, north of the northern abutment.
2. Reduced storage capacity at Beach Street / Canning Highway /Queen Victoria street intersection resulting in significant congestion.
3. Additional rail bridge required in 40 years (future proofing not considered)

	Environmental consideration		Residential consideration
	Heritage consideration		Proposed road alignment
	Port consideration		Proposed PSP alignment
	Rail consideration		Proposed road bridge
	Road consideration		
	Navigation consideration		



BETWEEN THE BRIDGES – One rail line bridge and road bridge

Strengths

- Able to construct new traffic bridge between existing bridges
- Bridge across the river moves further away from Rivershore Place (south facing) apartments (approximately 10m)
- Increase in freight and passenger rail capacity
- All new rail infrastructure retained within existing rail reserve
- No impact to port operations

Weaknesses

- When existing rail bridge needs to be replaced, not enough capacity for passage lines during construction
- No allowance for future proofing. Single track to be replaced with new 2 track bridge in 40 years' time
- PSP on the eastern side - New traffic bridge will need to be approx. 4m higher to allow for PSP underpass. This will impact access to local businesses on Queen Victoria Street and have significant visual impact on west facing Rivershore Place apartments
- Brings traffic light intersections at Canning Highway and Beach Street closer together and will increase congestion and traffic queuing during peak once complete
- Removal of heritage Ferry Capstan Base

BETWEEN THE BRIDGES – One rail line bridge and road bridge

Alternatives

- PSP can be constructed on western side of road bridge resulting in minimal need to raise bridge profile, minimised impact on access to local businesses on Queen Victoria Street

Building to the west



For illustrative purposes only


Key components

1. Pedestrian and cyclist path to go under road north of the northern abutment
2. Rail bridge (2 lines) to west of existing rail bridge
3. Road bridge (4-lanes + pedestrian and cyclist path) to west of existing road bridge
4. Option to retain Fremantle Traffic bridge for pedestrian and cyclist path
5. Delete existing dolphins and rock mound and add 6 new dolphins on western side of new rail bridge

Key considerations

1. Design standards and grade requirements for new freight rail bridge – significant replacement of rail infrastructure leading to and from rail bridge
2. Outside of rail reserve with impacts on Peter Hughes Drive, Gate 3 and port operations
3. Reduced storage capacity at Beach Street / Canning Highway / Queen Victoria street intersection resulting in significant congestion.
4. Cost





BRIDGE TO THE WEST

Strengths

- Able to keep current traffic bridge operating one lane in each direction during construction
- Bridge across the river moves further away from Rivershore Place (south facing) apartments (approximately 10m)
- Increase in freight and passenger rail capacity

Weaknesses

- Significant impact to port operations
- Reclamation of river required
- Significant increase in rail reservation needed
- Excises land from Fremantle Ports' Berth 12a, small craft pens and J-Berth
- Need to realign Gate 3 Accessway and rebuild Gate 3
- Relocation of small craft pen facility
- PSP on the eastern side - New traffic bridge will need to be approx. 4m higher to allow for PSP underpass. This will impact access to local businesses on Queen Victoria Street and have significant visual impact on west facing Rivershore Place apartments
- Reconstruction of bridge impact protection systems (rock mound and dolphins)- \$50M
- Brings traffic light intersections at Canning Highway and Beach Street closer together and will increase congestion and traffic queuing during peak once complete
- Removal of heritage Ferry Capstan Base

Building to the east



For illustrative purposes only

Key component

1. Tydemans Road bridge modification
2. Passenger rail bridge with two lines
3. Road bridge to include four traffic lanes and a six metre wide pedestrian and cycle path
4. Existing Fremantle Traffic Bridge to be demolished (excluding heritage remnant)

Dedicated freight line on retained Fremantle Rail Bridge

Key considerations

1. Proximity to residential apartments on Northern shore

 Environmental consideration	 Residential consideration
 Heritage consideration	 Proposed rail alignment
 Port consideration	 Proposed road alignment
 Rail consideration	 Proposed PSP alignment
 Road consideration	 Proposed road bridge
 Navigation consideration	 Proposed rail bridge



BRIDGE TO THE EAST

Strengths

- No impact on access to local businesses on Queen Victoria Street and no visual impact on west facing Rivershore Place apartments
- Increase in freight and passenger rail capacity
- All new rail infrastructure retained within existing rail reserve
- No impact to port operations
- Opportunities for activation in between bridges
- Protects ferry capstan base
- No impact on existing bridge protection systems
- Safer road intersection connection as it is further away from Beach Street
- No additional costs for port impacts as required in building a bridge to the west
- Minimal impact on small craft pens
- No reclamation of Swan River required

Weaknesses

- Bridge across the river moves closer to Rivershore Place (south facing) apartments (approximately 15m)