

AMENDMENTS APPROVED & DATE DESCRIPTION APPROACH AND TRAILING LENGTHS AMENDED, B. SNOOK 13/12/12 LAYOUT AMENDED TO INCORPORATE SPLICES LOCATED AT MIDSPAN.
TITLE BLOCK, FONT AND REFERENCES UPDATED. C. Mariano 9/11/23

NOTES

- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.
- BLOCKOUT TO BE APPROVED SOLID BLOCKOUT. REFER TO MRWA SPECIFICATION 603 ANNEXURE
- ONLY 'W' BEAM TYPE WW6 TO BE USED FOR THIS BARRIER CONFIGURATION.

W' BEAM TREATMENT SHALL ONLY BE USED WHERE IT IS DIFFICULT OR IMPOSSIBLE TO INSTALL A POST AT THE STANDARD SPACING, SUCH AS WHERE THERE IS A CLASH BETWEEN A POST AND A SERVICE.

THIS DRAWING SHALL BE READ IN CONJUNCTION

DRAWING

200331-0010 'W' BEAM - GENERAL ARRANGEMENT 200331-0013 'W' BEAM - FABRICATION DETAILS 200331-0014 'W' BEAM - STEEL POST & BLOCKOUT

FABRICATION DETAILS

200331-0016 BOLT, NUT & WASHER FABRICATION DETAILS

DRAWING SHALL BE READ IN CONJUNCTION WITH TECHNICAL SPECIFICATION





PLANNING AND TECHNICAL SERVICES DIRECTORATE ROAD AND TRAFFIC ENGINEERING BRANCH WATERLOO CRESCENT EAST PERTH 6004 Telephone 138 138

DRAWN **ROAD & TRAFFIC ENGINEERING** DESIGNED **ROAD & TRAFFIC ENGINEERING** VERIFIED 27/05/10

B. SNOOK APPROVED D LANDMARK A/MRTE 31/05/10 FILE NO. 13/4330

STANDARD DRAWING

SAFETY BARRIER 'W' BEAM TREATMENT 4000 CLEAR SPAN

201031-0030-2